data 2

Datasheet · Hardware product Monitor · June 2003

SCALEOVIEW C15-1
15 Inch LCD TFT Monitor

The Fujitsu Siemens monitors all stand for quality, reliability, ergonomics and environment compatibility. The new SCALEOVIEW C15-1 do not compromise on quality, features or style and is available for a very reasonable price. The SCALEOVIEW C15-1 is more than a monitor: this is a brand with a package full of features (slim, brilliant pictures, style and good sound).

- 15 inch LCD TFT display (comparable with 17 Inch CRT)
- High resolution XGA 1024 x 768 pixels
- High Brightness
- Light in weight
- Fast response time
- 16,2 mill. colors
- Optimum ergonomics ISO 13406-2 flicker-free and distortion-free
- Excellent focus and high contrast
- Low power consumption
- Two-level power management EPA, VESA DPMS
- Plug and Play VESA DDC 2B device
- Low-radiation and environmental friendly according to TCO'99
- Immune to external electromagnetic fields
- Multi-language OSD menu
- Auto-adjust
- Mechanical interface standardised according to VESA FPMPMI (75 mm)
- Integrated speakers

Data Sheet

www.fujitsu-siemens.com

FUJITSU COMPUTERS SIEMENS

Technical Data · SCALEOVIEW C15-1 · 15 Inch LCD TFT Monitor

Visible screen diagonal	**15 inch** (38 cm)
Graphics display (dependent on graphics processor)	
Pixels	1024 x 768
Pixels *)	800 x 600
Pixels *)	640 x 480
*) expanded	
Text display (dependent on graphics processor)	
Pixels (max. 75Hz)	720 x 400
Picture size	304 x 228 mm
Frequencies	
Horizontal	28 - 65 kHz
Vertical	56 - 78 Hz
Brightness typical	350 cd/m^2
Contrast typical	300:1
Viewing angle typical	
Horizontal	120°
Vertical	100°
Response time typical	30 ms
Plug and Play	VESA DDC2B

Setting options
Brightness (Back light)
Contrast
Picture position (horizontal and vertical)
Color temperature and individual color setting
Auto-adjust (direct access key)
Auto balance
Activate factory settings
Menu language,
13 pre-set modes and 10 user adjustable modes

Base	
Tilt angle	30 ° backward
Audio characteristics	
volume control	digital
Audio signal input (from PC)	3.5 mm stereo phone jack
Sound output	1 W (L) + 1 W (R)

Electrical values	
Rated voltage	100-240 V
Frequency	50-60 Hz
Power draw	
Max.	48 W
Stand by	< 3 W
Protection class	1
Temperatures/dimensions/weight	
Ambient temperature (to IEC721)	
Working	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D)	376 x 384 x 180 mm
Weight	3,5 kg
Reliability	
MTBF (demonstrated)	30,000 h
Lifetime of LCD backlight (brightness > 50 % of original brightness)	40,000 h
Compliance with standards	
Product safety	EN60950
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN55024 EN61000-3-2/-3); TCO'99
Data cable (1.8 m)	D-SUB (15-pin) **fixed** at monitor Audio cable (1.5 m)
Power cable (1.8 m)	For wall socket Euro-Schuko-Type CEE7
External power adapter	
Plug type on power adapter	IEC-320-C13
Special features	Standardized mounting interface according VESA FPMPMI (75 mm)
Order code	**S26361-K906-V200 or** **FSP: 840 002119** **EAN: 4 026227 021198**

Published by
Fujitsu Siemens Computers
Business Unit Consumer
Product Marketing

World Wide Web:
http://www.fujitsu-siemens.com

All rights, including rights created by patent grant or registration of a utility model or design, are reserved. Delivery subject to availability; right of technical modifications reserved.
All hardware and software names used are trade names or trademarks of their respective manufacturers.

Copyright ©
Fujitsu Siemens Computers GmbH, 06/2003

Company stamp